



8" Downlight
Ø8.7" x 4.4"

6" & 8" Options Available

COMMERCIAL DOWNLIGHTS

Wirelessly Controlled, Smart, Retrofit Downlights

APPLICATIONS: INDOOR LIGHTING, OFFICE, NEW CONSTRUCTION

The RCA Commercial Downlight is an unrivaled combination of lighting controls, efficacy and installation ease, bringing outstanding value to the downlight space. Our recessed parabolic downlight with trim ring features a beveled edge for clean ceiling interface.

- Plug-and-Play ZigBee Enabled Lighting Controls.
- Easy on Installers. Armored Cable system with Quick Connect Wiring.
- Mounts in drywall & grid ceiling applications with optional trim rings.
- High Efficacy light with external driver for retrofit and maintenance.

STANDARD FEATURES

Out-Of-The Box




FUTURE PROOF & SCALABLE

All Models, 6" & 8"

The commercial downlight performs true to spec out of the box. 0 - 10 V dimming capable & **Ready to make the Upgrade to LLLC when you are.**

LUMINAIRE LEVEL LIGHTING CONTROLS

Upgrade with Sensor Connect Smart Controls & Accessories



Requires | RCA-MULTI-SENSOR + LGE-CEILING-PLATE

A plug-and-play Multi-Sensor with tactile buttons for easy standalone lighting controls. Program min/max levels, motion detection and more.



Requires | RCA-MULTI-SENSOR + Android Phone

Convert your lights into a wireless mesh network using your Android Device. Group and commission your lighting network, and set up advanced LLLCs.

Ordering Information (For Manufacturing Part Numbers, Use Reference Chart on page 2)

Example: LGE-CRDL-16-35-1450-LGE-DW-TR-8


LGE	Product	Type	Size	CCT	Lumen Package	Options	
LGE	CRDL	Commercial Downlight	16	35	1450	RCA-MULTI-SENSOR Occupancy Sensor, Wireless Control (Optional)	LGE-DW-TR-8 Extended Trim Ring 6" Model Only
			6" Model 16 W	3500 K	1,450 lm *6" Only		
LGE	CRDL	Commercial Downlight	22	40	2000	LGE-DONGLE-VLC Wireless Communication Module	LGE-DW-TR-10 Extended Trim Ring 8" Model Only
			8" Model 22 W	4000 K	2,000 lm *8" Only		
						LGE-CEILING-PLATE Downlight Clip for Multi-Sensor	EM10W Emergency Pack 10 W / 90 Min

*2X2 models have limited power options and lumen packages available.


COMMERCIAL DOWNLIGHTS

Specs subject to change

Dimensions & Parts



Power	Lumens	Width (W)	Diameter (D)	Height (H)	Weight
16 W	1,450 lm	Ø7.0"	Ø6.0"	3.9"	1.87 lb
22 W	2,000 lm	Ø8.7"	Ø8.0"	4.3"	2.02 lb



Easy Installation

- Quickly connect LED Fixture Assembly with the driver assembly.
- Built In Connectors easily snap together
- Torsion Spring Retention Clips.

Options



Battery Backup	Smart Lighting Controls	Mounting Parts Field-Installable
EM10W Emergency Pack 10 W / 90 Min	RCA-MULTI-SENSOR Occupancy Sensor Wireless Control (Optional)	LGE-DW-TR-8 Extended Trim Ring 6" Model
	LGE-DONGLE-VLC Wireless Communication Only	LGE-DW-TR-10 Extended Trim Ring 8" Model
		LGE-CEILING-PLATE Ceiling Mount Plate Multi-Sensor

Lighting Specifications

Power Consumption	16 W	22 W
Max Delivered Lumens	1,450 lm	2,000 lm
Color Temperature	3500 K, 4000 K	
Optical Unit (Lens)	Frosted Polycarbonate	
Beam Angle	80°	
Efficacy	90 Lumens Per Watt	
Input Voltage	AC 120 - 277V, 50 - 60 Hz	
CRI	80 +	
L85 Lifetime	50,000 Hours at L85	
Controls	Sensor Connect, Smart Luco, VLC, 0 - 10 V	

Part Number Reference Chart

US Order Code	MPN #	US Order Code	MPN #
LGE-CRDL-16-35-1450	D1635RH8161	LGE-CRDL-22-35-2000	D2235RH7161
LGE-CRDL-16-40-1450	D1640RH8161	LGE-CRDL-22-40-2000	D2240RH7161

MPN = Manufacturer Part Number

Certifications & Warranty

cETLus Listed, UL 1598 Damp Location use. RoHS Compliant. Meets FCC Standards. Covered by RCA Commercial 5 Year Advanced Replacement Warranty.