




4' Model
(8' Model Available)



275° Beam Angle



**DLC 5.1
PREMIUM
LISTED**

SH SERIES WRAP | UPLIGHT

Super Wide Uplight, High Output LED Wraparound

APPLICATIONS: INDOOR, OFFICE, NEW CONSTRUCTION, WAREHOUSE

Powerfully efficient, the SH series covers more ambient surface area than its competitors, all at 120 Lumens per Watt. Models starting at 15,240 lumens, the SH series is a high output light engineered to cast light over a 275° area in large buildings, warehouses and factories.

Designed for Shipping & Sorting Areas. High Output LED Lighting.

Sealed fixture prevents dust and debris build up for easy maintenance.

Installer Friendly, quick access channel for end to end wiring.

Plug-and-Play ZigBee Enabled Lighting Controls.

STANDARD FEATURES

Out-Of-The Box



FUTURE PROOF & SCALABLE

SH Models, Out-of-the-Box

The SH Series performs true to spec out of the box. 0 - 10 V dimming capable & **Ready to make the Upgrade to LLLC when you are.**

LUMINAIRE LEVEL LIGHTING CONTROLS

Upgrade with Sensor Connect Smart Controls & Accessories



OCCUPANCY SENSING

Requires | SH Models or LGE-MULTI-SENSOR

Place the Multi-Sensor in SH Harness for easy standalone lighting controls. Program min/max levels, motion detection and more using tactile buttons



WIRELESS CONTROLS & OCCUPANCY SENSING

Requires | SH Model, Multi-Sensor & Android Phone

Convert your lights into a wireless mesh network using your Android Device. Group and commission your lighting network, and set up advanced LLLCs.

Ordering Information (Use Model Numbers column for ordering)

Example: SH8B2465SU50-RCA-MULTI-SENSOR

Product	Size	Model Number	Watts	CCT	Lumens	Beam	Driver	Options
SH Series High Output Uplight Strip Light	4' Ft.	SH4B3432SU35*	120 W	3500 K	16,979 lm	275°	Universal AC 120- 277 V 50 - 60 Hz	RCA-MULTI-SENSOR Occupancy Sensor, Wireless Control (Optional) LGE-DONGLE-VLC Wireless Communication Module RCA-DIM-MODULE 0 - 10V Dimming Driver Module
		SH4B3432SU40*	120 W	4000 K	17,204 lm			
		SH4B3432SU50	120 W	5000 K	17,428 lm			
	8' Ft.	SH8B2465SU35*	150 W	3500 K	26,609 lm	275°	Universal AC 120- 277 V 50 - 60 Hz	
		SH8B2465SU40*	150 W	4000 K	27,617 lm			
		SH8B2465SU50	150 W	5000 K	27,334 lm			
							SC-SMAH Multi-Sensor Harness, Required for Multi-Sensor RCA-AC Cable Mount Kit All Models EM25W Emergency Pack 25W / 90 Min	

*3500 K & 4000 K Color Temperatures available with Custom Orders. Contact your sales rep for more information.

SH SERIES WRAP | HIGH OUTPUT UPLIGHT

Specs subject to change

Dimensions, Parts & Knockouts



Dimensions : 4' & 8'



Size	Width (W)	Length (L)	Height (H)	Weight
4 ft	5.3"	47.24"	3.0"	5.73 lbs
8 ft	5.3"	94.49"	3.0"	11.6 lbs

Size	Gap (G)	Knockout Size (K)	Mounting (M)
4 ft	21.95"	3/4"	2.08"
8 ft	35.95"	3/4"	2.08"

Knockouts : 4' & 8'



Long Wiring Channel

- Easy access wiring channel on back of fixture
- Wagos Connectors Included for quick install
- 3/4" Knockouts in middle and ends for wiring.

Options



Battery Backup	Smart Lighting Controls				Mounting Kits	
EM25W Emergency Pack 25W / 90 Min	RCA-MULTI-SENSOR Occupancy Sensor Wireless Control (Optional)	LGE-DONGLE-VLC Wireless Communication Only	RCA-DIM-MODULE Dimming Driver Module	SC-SMAH Multi-Sensor Wired Harness, Included on ST/SD Models	RCA-LINEAR-EP Standard Endplate for Linears w/o SC-SMAH Harness	RCA-AC Cable Mount Kit All Models


Lighting Specifications

Size	4'	8'
Power Consumption	Up to 120 W	Up to 150 W
Max Delivered Lumens	Up to 17,428 lm	Up to 27,617 lm
Color Temperature	3500 K, 4000 K, 5000 K	
Optical Unit (Lens)	Frosted Polycarbonate	
Beam Angle	275° High Output Uplight	
Efficacy	Up to 182 Lumens Per Watt	
Input Voltage	AC 120 - 277V, 50 - 60 Hz	
CRI	83 +	
L80 Lifetime	50,000 Hours at L80	
Controls	Sensor Connect, Smart Luco, VLC, 0 - 10 V	
Mounting	Surface Mount, Suspended	

DLC Product ID Reference Chart

US Order Code	DLC Prod. ID	US Order Code	DLC Prod. ID
SH4B3432SU35	S-2EXG8B	SH8B2465SU35	S-TJ7AM4
SH4B3432SU40	S-R028AQ	SH8B2465SU40	S-4AHD7L
SH4B3432SU50	S-J5GASU	SH8B2465SU50	S-MZFJ17

Linear Light Beam Angles



Certifications & Warranty

DLC 5.1 Premium Listed, cULus Listed, UL 1598 Damp Location Use, RoHS Compliant, Meets FCC Standards, Trade Agreement Act Compliant, Covered by RCA Commercial 5 Year Advanced Replacement Warranty.